



SAFETY DATA SHEET TERMINATOR

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name TERMINATOR

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Pesticide

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier PelGar International Ltd
Unit 13
Newman Lane
Alton
Hampshire
GU34 2QR
United Kingdom
Telephone : +44(0)1420 80744
E-mail: garry@pelgar.co.uk

1.4. Emergency telephone number

Emergency telephone +44(0)1420 80744

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 3 - H226

Health hazards Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Muta. 1B - H340 Carc. 1B - H350
STOT SE 3 - H335 Asp. Tox. 1 - H304

Environmental hazards Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

2.2. Label elements

Pictogram



Signal word

Danger

TERMINATOR

Hazard statements

H332 Harmful if inhaled.
 H304 May be fatal if swallowed and enters airways.
 H350 May cause cancer.
 H335 May cause respiratory irritation.
 H315 Causes skin irritation.
 H340 May cause genetic defects.
 H318 Causes serious eye damage.
 H410 Very toxic to aquatic life with long lasting effects.
 H226 Flammable liquid and vapour.

Precautionary statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing vapour/spray.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P312 Call a POISON CENTER/doctor if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P331 Do NOT induce vomiting.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P391 Collect spillage.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with national regulations.

Contains

SOLVENT NAPHTHA, LIGHT, 1,2,4-TRIMETHYLBENZENE, CYPERMETHRIN, DODECYLBENZENE SULPHONATE CALCIUM SALT, BUTANOL-norm

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TERMINATOR

SOLVENT NAPHTHA, LIGHT	30-60%
CAS number: 64742-95-6	EC number: 265-199-0
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Muta. 1B - H340 Carc. 1B - H350 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
1,2,4-TRIMETHYLBENZENE	10-30%
CAS number: 95-63-6	EC number: 202-436-9
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
CYPERMETHRIN	10-30%
CAS number: 52315-07-8	EC number: 257-842-9
M factor (Acute) = 1000	M factor (Chronic) = 1000
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Acute Tox. 4 - H332 STOT SE 3 - H335 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	
DODECYLBENZENE SULPHONATE CALCIUM SALT	1-5%
CAS number: 90194-26-6	EC number: 290-635-1
Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Dam. 1 - H318	

TERMINATOR

BUTANOL-norm	1-5%
CAS number: 71-36-3	EC number: 200-751-6
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Acute Tox. 4 - H302 STOT SE 3 - H335, H336 STOT SE 3 - H335, H336 STOT SE 3 - H335, H336	
ALCOHOL ETHOXYLATE	<1%
CAS number: 68131-39-5	
Classification Acute Tox. 4 - H302 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention.
Ingestion	Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not induce vomiting. Get medical attention immediately. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.

TERMINATOR

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.2. Environmental precautions

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid the spillage or runoff entering drains, sewers or watercourses. Inform authorities if large amounts are involved.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Avoid contact with skin and eyes. Avoid spilling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BUTANOL-norm

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m³(Sk)

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Use protective gloves.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Promptly remove any clothing that becomes contaminated. Wash promptly with soap and water if skin becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Wash hands at the end of each work shift and before eating, smoking and using the toilet.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

TERMINATOR

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Brown.
Odour	Aromatic.
Odour threshold	No information available.
pH	No information available.
Melting point	No information available.
Initial boiling point and range	No information available.
Flash point	~ 50°C TCC (Tag closed cup).
Evaporation rate	No information available.
Evaporation factor	No information available.
Upper/lower flammability or explosive limits	No information available.
Vapour pressure	No information available.
Vapour density	No information available.
Relative density	0.93 @ @ 20°C
Bulk density	No information available.
Solubility(ies)	Forms an emulsion with water. Soluble in the following materials: Organic solvents.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Viscosity	No information available.
Explosive properties	Not considered to be explosive.
Oxidising properties	Not oxidising.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with the following materials:
Acids. Oxidising agents.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO₂).

TERMINATOR

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 3,816.79

Acute toxicity - dermal

ATE dermal (mg/kg) 14,814.81

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Harmful.

ATE inhalation (gases ppm) 12,233.58

ATE inhalation (vapours mg/l) 29.9

ATE inhalation (dusts/mists mg/l) 3.77

Skin corrosion/irritation

Skin corrosion/irritation Very irritating to Skin.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye damage.

Germ cell mutagenicity

Genotoxicity - in vivo Suspected of causing genetic defects.

Carcinogenicity

Carcinogenicity Suspected of causing cancer.

Specific target organ toxicity - single exposure

STOT - single exposure May cause respiratory irritation.

Acute and chronic health hazards Harmful by inhalation. May cause respiratory system irritation. SKIN CONTACT. Product has a defatting effect on skin. Prolonged or repeated exposure may cause severe irritation. EYE CONTACT. May cause serious eye damage. Aspiration Hazard.

Target organs Skin Eyes Respiratory system, lungs

SECTION 12: Ecological Information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

12.1. Toxicity

Toxicity Toxic to fish.

12.2. Persistence and degradability

12.3. Bioaccumulative potential

Partition coefficient No information available.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

TERMINATOR

Disposal methods Dispose of in accordance with applicable regional, national, and local laws and regulations.
Dispose of Contaminated packaging as unused product unless fully cleaned.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID)	1993
UN No. (IMDG)	1993
UN No. (ICAO)	1993
UN No. (ADN)	1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, N.O.S. (CONTAINS SOLVENT NAPHTHA (LIGHT), 1,2,4-TRIMETHYL BENZENE AND n-BUTANOL)
Proper shipping name (IMDG)	FLAMMABLE LIQUID, N.O.S. (CONTAINS SOLVENT NAPHTHA (LIGHT), 1,2,4-TRIMETHYL BENZENE AND n-BUTANOL)
Proper shipping name (ICAO)	FLAMMABLE LIQUID, N.O.S. (CONTAINS SOLVENT NAPHTHA (LIGHT), 1,2,4-TRIMETHYL BENZENE AND n-BUTANOL)
Proper shipping name (ADN)	FLAMMABLE LIQUID, N.O.S. (CONTAINS SOLVENT NAPHTHA (LIGHT), 1,2,4-TRIMETHYL BENZENE AND n-BUTANOL)

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

TERMINATOR

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	The information contained in this Safety Data Sheet is believed to be true and correct, as of the issue date. The accuracy and completeness of this information and any recommendations, or suggestions are made without warranty or guarantee. Since the conditions of use are beyond the control of our company, it is the responsibility of the user to determine the conditions of safe use for this product.
Revision comments	Risks recalculated to ensure data is up to date
Revision date	26/05/2016
Revision	2
Supersedes date	26/05/2016
SDS number	20676
Hazard statements in full	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H340 May cause genetic defects. H350 May cause cancer. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.